

Metric Specifications:

Model BS	Working Length mm	Bending Capacity		Slitting Capacity		No. of Stand and Tension Arm Units	No. of driven linkage assemblies	Hydraulic Motor Size Kw	Length with Motorized Shear mm	Approx. Weight kg
		Steel N/mm ²	Alu N/mm ²	Steel N/mm ²	Alu N/mm ²					
3.2,00	3100	2,00	3,00	2,00	2,50	3	5	3,0	4500	3000
4.2,00	4010	2,00	3,00	2,00	2,50	4	7	4,0	5500	4000
6.2,00	6200	2,00	3,00	2,00	2,50	6	11	5,5	7700	5500
8.2,00	8020	2,00	3,00	2,00	2,50	8	15	7,5	9500	7500
10.2,00	10020	2,00	3,00	2,00	2,50	10	19	11,0	11500	9500
12.2,00	12020	2,00	3,00	2,00	2,50	12	23	15,0	13500	10500
4.3,00	4010	3,00	4,00	2,00	2,50	6	13	5,5	5500	5000
6.3,00	6200	3,00	4,00	2,00	2,50	8	17	7,5	7700	7000
8.3,00	8020	3,00	4,00	2,00	2,50	11	23	11,0	9500	9000

US Specifications

Model BS	Working Length inches	Bending Capacity		Slitting Capacity		No. of Stand and Tension Arm Units	No. of driven linkage assemblies	Hydraulic Motor Size Kw	Length with Motorized Shear inches	Approx. Weight Lbs.
		Steel gauge	Alu inches	Steel gauge	Alu inches					
3.2,00	118	14	.12	14	.10	3	5	3.0	177	6.600
4.2,00	157	14	.12	14	.10	4	7	4.0	217	8.800
6.2,00	252	14	.12	14	.10	6	11	5.5	304	12.000
8.2,00	315	14	.12	14	.10	8	15	7.5	374	16.500
10.2,00	394	14	.12	14	.10	10	19	11.0	453	21.000
12.2,00	473	14	.12	14	.10	12	23	15.0	532	23.000
4.3,00	157	12	.16	14	.10	6	13	5.5	217	11.000
6.3,00	252	12	.16	14	.10	8	17	7.5	304	15.500
8.3,00	315	12	.16	14	.10	11	23	11.0	374	20.000